

Product Application

The SS secure floor strapping prevents uplift of wall studs from floor track, creating a secure composite assembly. It's provided in 18", 24", 30", and 36" lengths with a specific layout of pre-punched guide holes for ultimate reinforcing and efficient installation.

Features and Benefits

- Variety of lengths available
- Pre-punched guide holes
- Prevents uplift of studs

Material Composition

- Mill certified steel
- ASTM A653/A653M
- 33 mil
 - 33 ksi yield strength
 - 45 ksi tensile strength
 - G60 galvanized coating
- 43 mil
 - 33 ksi yield strength
 - 45 ksi tensile strength
 - G60 galvanized coating
- 54 mil
 - 57 ksi yield strength
 - 65 ksi tensile strength
 - G60 galvanized coating
- 68 mil
 - 57 ksi yield strength
 - 65 ksi tensile strength
 - G90 galvanized coating

Quantity / Order Information

Part No.	Dimensions	
	Width	Height = xx
125SSxx-33	1 ¼"	18", 24", 30", 36"
125SSxx-43	1 ¼"	18", 24", 30", 36"
125SSxx-54	1 ¼"	18", 24", 30", 36"
125SSxx-68	1 ¼"	18", 24", 30", 36"
125SSxx-97	1 ¼"	18", 24", 30", 36"
275SSxx-33	2 ¾"	18", 24", 30", 36"
275SSxx-43	2 ¾"	18", 24", 30", 36"
275SSxx-54	2 ¾"	18", 24", 30", 36"
275SSxx-68	2 ¾"	18", 24", 30", 36"
275SSxx-97	2 ¾"	18", 24", 30", 36"

